

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://microsensor.nt-rt.ru/> || moj@nt-rt.ru

Интеллектуальный датчик уровня MDM7000-LT. Технические характеристики.



Range

Nominal range	Minimum range	Lower (LRL)	Upper (URL)
0.4bar	0.1bar	-0.4bar	0.4bar
2.5bar	0.25bar	-2.5bar	2.5bar

LRV/URV setting: the lower limit value (LRV) and upper limit value (URV) are achieved between the upper and lower limits. If $|URV| \geq |LRV|$, $|URV|$ must be larger than the minimum pressure; if $|URV| \leq |LRV|$, $|LRV|$ must be larger than the minimum pressure.
It is recommended to choose a range ratio with the minimum possible value.

Accuracy

1 Stated reference accuracy include best fit straight line(BFSL), hysteresis, and repeatability as per the standard and reference test conditions.
Calibration temperature: 20°C ±5°C, based on Zero value.

2 Total performance is based on combined errors of indoor temperature accuracy, ambient temperature effects and static pressure effects, calculated by the following formula: Total performance = $\pm\sqrt{(E1)^2 + (E2)^2 + (E3)^2}$;

E1=Indoor temperature accuracy E2=Ambient temperature effects E3=Static pressure effects

Linear output accuracy	TD ^① ≤5	±0.25%+Diaphragm seal system effects	0.4bar, 2.5bar
	TD>5	±(0.025×0.045TD% + Diaphragm seal system effects	

Square root output accuracy is 1.5 times linear output accuracy.

Note: ^①TD(Turn down) represents the range ratio, TD= Maximum range / Current range
[Maximum range = URL (range starts with 0, same as factory calibration range); Current range = SPAN (equivalent to |URV-LRV|)].

Specifications

Accuracy	±0.2% URL + Diaphragm seal system effects
Range	0.4bar~2.5bar, see the specifications for details
Long-term stability	±0.2% Span/5 years
Ambient temperature effects	The total effect per 10°C in the range of -20°C ~80°C: (0.375+0.125TD)%/10°C of SPAN
Voltage effects	When the power supply voltage changes within 10.5V/16.5V ~55V DC, its zero point and range change should not exceed ±0.005% URL/V
Mounting position effects	The installation of the transmitter may produce a zero point error, which can be corrected by PV (primary value) =0 reset without any effect on the range.
Vibration effects	< 0.1% SPAN as per GB/T18271.3/IEC61298-3
Output signal	4mA~20mA DC, HART
IP rating	IP67
Weight	With DN50 flange: About 12.6kg (excluding capillary tube) With DN80 flange: About 15.5kg (excluding capillary tube)

Note: ^①The accuracy is dependent on the range. Please consult the engineer for details.
^② 16.5V is the voltage required for adding a 250 Ω resistor to the HART carrier.

EMC Effects

SN	Test items	Basic Standards	Test Conditions	Performance Level
1	Radiated interference (case)	GB/T 9254.1/CISPR 32	30MHz~1000MHz	Qualified
2	Conducted interference (DC power port)	GB/T 9254.1/CISPR 32	0.15MHz~30MHz	Qualified
3	Electrostatic discharge (ESD) immunity test	GB/T 17626.2/IEC61000-4-2	4kV(Contact), 6kV(Air)	B
4	Radiated, radio-frequency, electromagnetic field immunity test	GB/T 17626.3/IEC61000-4-3	10V/m (80MHz~1GHz)	A
5	Power frequency magnetic field immunity test	GB/T 17626.8/IEC61000-4-8	30A/m	A
6	Electrical fast transient / burst immunity test	GB/T 17626.4/IEC61000-4-4	2kV(5/50ns,100kHz)	B
7	Surge immunity test	GB/T 17626.5/IEC61000-4-5	500V(line to line) 1kV(line to ground) (1.2/50μs)	B
8	Immunity to conducted disturbances induced by radio frequency fields	GB/T 17626.6/IEC61000-4-6	3V(150kHz~80MHz)	A

Note: At performance level A, the performance is normal within the limits of the technical specifications.
At performance level B, functions or performance are temporarily reduced or lost, but can be restored by themselves, and the actual operating conditions, storage and data remain unchanged.

|| Environmental Conditions ||

Items	Conditions
Operating temperature	Without LCD display: -40°C ~85°C ; with LCD display: -20°C ~70°C
Storage temperature	Without LCD display: -40°C ~100°C ; with LCD display: -40°C ~85°C
Operating humidity	5%RH~100%RH@40°C


|| Diaphragm Operating Temperature ||

Filling oil type ^①	Code	Medium temperature	Diaphragm ambient temperature
Normal temperature silicone oil	S	-40°C ~ 205°C	-40°C ~ 85°C
Inert filling oil	D	-45°C ~ 160°C	-40°C ~ 85°C
High temperature silicone oil	H	0°C ~ 315°C	0°C ~ 85°C

Note: ^① This item is related to the type of silicone oil filled and the o- ring; the temperature range of non-silicone oil is limited to the lowest material temperature range in the system. For short-pipe explosion-proof products, users need to ensure that the surface temperature of the shell is not higher than 80° C. If uncertain, the medium temperature must be ensured not to be higher than the T6/T80° C temperature group.

|| Power Supply and Load Requirements ||

Items	Conditions
Power supply voltage	HART communication protocol: 16.5V~55V DC ^① Intrinsically safe HART communication protocol: 18.5V~28V DC
Load resistance	0Ω~2119Ω ^② for operation mode; 250Ω~600Ω for HART communication
Transmission distance	<1000m
Power consumption	
4mA~20mA	≤500mW@24V DC, 20.8mA



Note: ^① Non intrinsically safe power supply voltage can be selected as 10.5V. Please consult engineers for details.

^② 2119Ω= (55V-10.5V) /21mA

|| Time Index ||

Damping time constant: equals to the combined damping time of electronic components and sensor module
Electronic components damping time: 0s~100s configurable
Sensor module damping time(sensor isolated diaphragm and filled silicone oil):≤ 0.2s (Note: This item is related to the sensor type and whether there is a diaphragm component.)
Turn-on time: ≤6s
Factory reset time: ≤31s


|| Hazardous Area ||

Hazardous area ^①	PCEC	Ex db IIC T6 Gb Ex ia IIC T4 Ga
	NEPSI	Ex tb III C T85°C Db
	ATEX	Ex ia IIC T4 Ga II 2G Ex db IIC T6 Gb II 2D Ex tb IIIC T80°C Db
	IECEX	Ex ia IIC T4 Ga Ex db IIC T6 Gb Ex tb IIIC T80°C Db
	CSA	Class I, Division 1, Group A, B, C and D T6 Class II, Division 1 Group E, F and G T80°C Class III Ex db IIC T6 Gb Class I, Zone 1, AEx db IIC T6 Gb Ex tb IIIC T80°C Db Zone 21, AEx tb IIIC T80°C Db
Note: ^① Please consult engineers for details.		


Unit: mm

Note: The gland head is sent as an accessory with the product when it leaves the factory, and it is to be installed by the user.


Side Mounted Flange With Display (Same as Without Display)




Side Mounted Flange Insertion Sleeve With Display (Same as Without Display)




Remote Flange With Display (Same as Without Display)



Remote Flange Insertion Sleeve With Display (Same as Without Display)



Process Connection



Standard	Specification	Outer diameter (φD)	Thickness (B)	Hole circumference (φK)
HG/T20592-2009	DN50PN10	165	20	125
HG/T20592-2009	DN80PN10	200	20	160
HG/T20592-2009	DN100PN10	220	20	180
RF diameter (φG)	Hole diameter (φH)	Quantity (n)	Corrugation diameter (φM)	
102	18	4	56	
138	18	8	56	
158	18	8	56	

Process Connection					
Standard	Specification	Outer diameter(φD)	Thickness(B)	RF diameter(φG)	Hole circumference (φK)
HG/T20592-2009	DN80PN10	200	20	138	160
HG/T20592-2009	DN80PN10	200	20	138	160
HG/T20592-2009	DN80PN10	200	20	138	160
HG/T20592-2009	DN50PN10	165	20	102	125
HG/T20592-2009	DN50PN10	165	20	102	125
HG/T20592-2009	DN50PN10	165	20	102	125
Quantity (n)	Hole diameter (φH)	Insertion sleeve diameter (φP)	Insertion sleeve length (L)	Corrugation diameter (φM)	
8	18	66	50	42	
8	18	66	100	42	
8	18	66	150	42	
4	18	46	150	42	
4	18	46	50	42	
4	18	46	100	42	

|| Order Guide ||

MDM7000-LT — □□□□□ — □ — HN — □□□□□□□□ — □□□□□

Body

Side Mounted Movable Flange Diaphragm

Item	Code	Description
MDM7000-LT	—	Monocrystalline Silicon Differential Pressure Transmitter Side Mounted Diaphragm Seal (Side Mounted Movable Flange Insertion Sleeve)

Application of hazardous area

1	China, Flameproof certificate, No.CE23.6650 Ex db IIC T6 Gb, GB/T3836.1-2021, GB/T3836.2-2021	
2	China, Intrinsically safe certificate, No.CE23.7688X Ex ia IIC T4 Ga, GB/T3836.1-2021, GB/T3836.4-2021	
3	China, Dust explosion-proof certificate, GYB24.1215X Ex tb III C T85°C Db, GB/T3836.1-2021, GB/T 3836.31-2021	
4	China, Flameproof certificate, Intrinsically safe certificate	
A	CSA, Flameproof certificate	
B	CSA, Intrinsically safe certificate	
C	CSA, Flameproof certificate, Intrinsically safe certificate	
E	ATEX, Flameproof certificate	
F	ATEX, Intrinsically safe certificate	
G	ATEX, Flameproof certificate, Intrinsically safe certificate	
J	IECEx, Flameproof certificate	
K	IECEx, Intrinsically safe certificate	
L	IECEx, Flameproof certificate, Intrinsically safe certificate	 
0	Non-hazardous area	
T	Other certificate	

Output signal	H	4mA ~ 20mA DC, HART	
---------------	---	---------------------	---

Case	S	Stainless steel case with two outlet ports (F) M20×1.5	
	U	Stainless steel case with two outlet ports (F) 1/2NPT	
	P	Aluminum alloy case with two outlet ports (F) M20×1.5	
	N	Aluminum alloy case with two outlet ports (F) 1/2NPT	

Note: Please pay attention to the item of lithium battery (Code: LD)

Waterproof/Explosion-proof connector

	Specification	Material	Applicable wire diameter	IP rating	
1	M20×1.5 waterproof connector, with plug	PVC	6mm~8mm	IP67	
2	Non-flameproof adapter (F) M20×1.5, with plug	316 SS	6mm~8mm	IP67	
3	Flameproof adapter (F) 1/2NPT, with plug	316 SS	6mm~8mm	IP67	
4	Flameproof adapter (F) M20×1.5, with plug	316 SS	6mm~8mm	IP67	
5	Flameproof adapter (F) G1/2, with plug	316 SS	6mm~8mm	IP67	

Note: Flameproof configuration is applicable to PCEC/ATEX/IECEx standards. Flameproof adapter with CCC certificate. Please contact the engineer if double sealing is required.

Display	N	Without LCD display	
	L	Display module, -20°C ~70°C	

Sensor module range

	Nominal range	Minimum range	Lower (LRL)	Upper (URL)
2	0.4bar	0.1bar	-0.4bar	0.4bar
3	2.5bar	0.25bar	-2.5bar	2.5bar

Low pressure side wetted parts

		Diaphragm	Flange block	Discharge valve/plug	Sealings
	A	316L	316	316	FKM
	B	316L	316	316	Glass-filled PTFE
	C	HC-276	316	316	FKM
	D	HC-276	316	316	Glass-filled PTFE

Low pressure side clamp flange process connection		Specifications	Drain/vent valve position	Thread	Mounting method	
	2	Female 1/4-18NPT	Above the side of flange	7/16-20UNF (F)	Horizontal	
	3	Female 1/4-18NPT	Under the side of flange	7/16-20UNF(F)	Horizontal	

Low pressure side fill oil	S	Normal temperature silicone oil (Medium temperature : -40°C ~205°C ,diaphragm ambient environment: -40°C ~85°C)				
	D	Inert oil (Medium temperature : -45°C ~160°C ,diaphragm ambient environment: -40°C ~85°C)				
	H	High temperature silicone oil (Medium temperature: 0°C ~315°C , diaphragm ambient environment: 0°C ~85°C)				

Clamp flange fastener	6	Bolts, nuts and other assemblies, 316 SS				
-----------------------	---	--	--	--	--	--

Diaphragm connection position	H	Differential pressure transmitter high pressure side				
Diaphragm seal system code	N	Side mounted movable flange insertion sleeve				

Flange standard	2	HG/T-20592				
	1	EN1092-1				
	5	HG/T-20615				
	6	ANSI/ASME B16.5				

Flange diameter			Applicable standard			
	B	DN50	HG/T-20592, EN1092-1			
	C	DN80	HG/T-20592, EN1092-1			
	D	DN100	HG/T-20592, EN1092-1			
	2	2inch	HG/T-20615, ANSI/ASME B16.5			
	3	3inch	HG/T-20615, ANSI/ASME B16.5			
	4	4inch	HG/T-20615, ANSI/ASME B16.5			

Pressure class			Applicable standard		Applicable flange diameter	
	1	PN10/PN16	HG/T-20592, EN1092-1		DN50, DN80, DN100	
	2	PN25/PN40	HG/T-20592, EN1092-1		DN50, DN80, DN100	
	3	PN63	HG/T-20592, EN1092-1		DN50, DN80	
	4	PN100	HG/T-20592, EN1092-1		DN50, DN80	
	A	Class 150	HG/T-20615, ANSI/ASME B16.5		2inch, 3inch, 4inch	
	B	Class 300	HG/T-20615, ANSI/ASME B16.5		2inch, 3inch, 4inch	
	C	Class 600	HG/T-20615, ANSI/ASME B16.5		2inch, 3inch	

Note: The maximum static pressure or overload depends on the flange pressure class

Flange material	6	316 SS				
Blind sealing surface	1	RF Raised surface				
	A	FM Concave surface				
	B	M Convex surface				
	C	RJ Annular connection surface				

Note: For details about FM concave, M convex, RJ annular connection surface, please consult the engineer

Wetted parts material	Please see the material list of wetted parts for details	
	Blind	Measuring diaphragm
6A	316 SS	316L
6B	316 SS	Hastelloy C-276
6C	316 SS	Tantalum
6D	316 SS	Titanium
6E	316 SS	Monel
High pressure side fill oil	S	Normal temperature silicone oil (Medium temperature : -40°C ~205°C ,diaphragm ambient environment: -40°C ~85°C)
	D	Inert oil (Medium temperature :-45°C ~160°C ,diaphragm ambient environment:-40°C ~85°C)
	H	High temperature silicone oil (Medium temperature:0°C ~315°C ,diaphragm ambient environment:0°C ~85°C)
Factory calibration range	CAL	Provides Micro Sensor standard verification report according to the range, and the default linear output Contract specifies: LRL - URL, display unit*
Options	Description (Detailed specifications as following, multiple options or null)	
High vacuum high temperature	/V	High vacuum and high temperature process diaphragm (if this option is selected, the accuracy will be affected and can only up to 0.2%)
Process connection accessories	/D1	T-shaped adapter (M) M20×1.5 and vent tube Φ14mm× 2mm× 30mm, 30, 316 SS
	/D2	Waist-shaped adapter, 1/2-14NPT (F), 316SS
Verification report	/Q1	Provide the Micro Sensor verification data according to user requirements Contract specifies: LRL - URL, display unit*
Note: Standard format follows the Micro Sensor's specifications. Select this option and provide the template if the customer specifies a format		
Damping time setting	/ST	Adjustable range 0s~100s, default 0s Contract specifies: Damping time*
Fault alarm setting	/WH	High alarm current value, 20.8mA
	/WL	Low alarm current value, 3.8mA, default
	/WS	Other saturation current values, specified within the range of 3.6mA~3.8mA or 20mA~22mA Contract specifies: saturation current values *
Product certificate	/QE	Standard format follows the Micro Sensor's specifications. Select this option and provide the template if the customer specifies a format
Identification plate	/PT	Product is shipped with an identification plate Contract specifies: Identification number, not exceeding 16 characters
Integrated valve manifold	/VT	Differential pressure transmitter is factory assembled with Micro Sensor valve manifold See attachment for order guide of valve manifold Contract specifies: Complete model of Micro Sensor valve manifold*
Leakage test report	/QD4	PN10/PN16 (class150) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD5	PN25/PN40 (class300) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD6	PN63, Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD7	PN100 (class600) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
Note: The test pressure is the same as the flange pressure class		
HART configuration	/H5	HART5 configuration
Diaphragm with gold plated	/J3	Single diaphragm on high pressure side (5μ)
	/J4	Double diaphragms on high and low pressure sides (5μ)
Diaphragm spraying	/T1	High pressure side single flange
Diaphragm sticking	/PFA	The diaphragm is stuck with PFA film, applicable to non-vacuum situations (pressure ≥ 0)
Oil-free treatment	/CL1	Degreasing and cleaning treatment of the wetted parts
Note: Please check the fill oil. Determine whether the inert filling oil is required (code: D)		



Certificates	/CS1	CCS, China Classification Society, TJ23PTB00014	
	/CS2	DNV, Det Norske Veritas	
	/CS3	BV, Bureau Veritas	
	/CS4	ABS, American Bureau of Shipping	
	/CS5	LR, Lloyd's Register of Shipping	
	/CS6	KR, Korean Register of Shipping	
	/CS7	NK, Nippon Kaiji Kyokai	
	/CS8	RS, Russian Maritime Register of Shipping	

Note: Except for the CCS certificate, please consult the engineer for others.

Lithium battery	/LD	General requirements for low copper and zinc in the lithium battery industry
High-accuracy	/HAC	High-accuracy calibration according to the user's specified range Contract specifies: Range of use (within sensor's limit), LRL-URL, display unit, accuracy *
Language	/LE	English nameplate, operation manual, product certificate, etc.
Delivery service	/XM	Provide customer requested content according to project delivery standards
Extended warranty period	/Y3	3-year warranty
	/Y5	5-year warranty

***Note:** The specifications required for these options should be specified in the contract

Example : MDM7000-LT-0HP1L-2A2S1-HN-2B14616AS/D1- 【CAL: 0-0.4bar】

|| Order Guide ||


MDM7000-LT — □□□□□ — □ — HM — □□□□□□□□ — □□□□□

Body

Side Mounted Movable Flange Diaphragm

Item	Code	Description	
MDM7000-LT	—	Monocrystalline Silicon Differential Pressure Transmitter Side Mounted Diaphragm Seal (Side Mounted Movable Flange Insertion Sleeve)	
Application of hazardous area			
	1	China, Flameproof certificate, No.CE23.6650 Ex db IIC T6 Gb, GB/T3836.1-2021, GB/T3836.2-2021	
	2	China, Intrinsically safe certificate, No.CE23.7688X Ex ia IIC T4 Ga, GB/T3836.1-2021, GB/T3836.4-2021	
	3	China, Dust explosion-proof certificate, GYB24.1215X Ex tb III C T85°C Db, GB/T3836.1-2021, GB/T 3836.31-2021	
	4	China, Flameproof certificate, Intrinsically safe certificate	
	A	CSA, Flameproof certificate	
	B	CSA, Intrinsically safe certificate	
	C	CSA, Flameproof certificate, Intrinsically safe certificate	
	E	ATEX, Flameproof certificate	
	F	ATEX, Intrinsically safe certificate	
	G	ATEX, Flameproof certificate, Intrinsically safe certificate	
	J	IECEx, Flameproof certificate	
	K	IECEx, Intrinsically safe certificate	
	L	IECEx, Flameproof certificate, Intrinsically safe certificate	
	O	Non-hazardous area	
	T	Other certificate	
Output signal	H	4mA~20mA DC, HART	
Case	S	Stainless steel case with two outlet ports (F) M20×1.5	
	U	Stainless steel case with two outlet ports (F) 1/2NPT	
	P	Aluminum alloy case with two outlet ports (F) M20×1.5	
	N	Aluminum alloy case with two outlet ports (F) 1/2NPT	
Note: Please pay attention to the item of lithium battery (Code: LD)			
Waterproof/explosion-proof connector			
		Specification	Material
	1	M20×1.5 waterproof connector, with plug	PVC
	2	Non-flameproof adapter (F) M20×1.5, with plug	316 SS
	3	Flameproof adapter (F) 1/2NPT, with plug	316 SS
	4	Flameproof adapter (F) M20×1.5, with plug	316 SS
	5	Flameproof adapter (F) G1/2, with plug	316 SS
		Applicable wire diameter	IP rating
	1	6mm~8mm	IP67
	2	6mm~8mm	IP67
	3	6mm~8mm	IP67
	4	6mm~8mm	IP67
	5	6mm~8mm	IP67
Note: Flameproof configuration is applicable to PCEC/ATEX/IECEx standards. Flameproof adapter with CCC certificate. Please contact the engineer if double sealing is required.			
Display	N	Without LCD display	
	L	Display module, -20°C ~70°C	
Sensor module range			
		Nominal range	Minimum range
	2	0.4bar	0.1bar
	3	2.5bar	0.25bar
		Lower (LRL)	Upper (URL)
	2	-0.4bar	0.4bar
	3	-2.5bar	2.5bar

Low pressure side wetted parts		Diaphragm	Flange block	Discharge valve/plug	Sealings
	A	316L	316	316	FKM
	B	316L	316	316	Glass-filled PTFE
	C	HC-276	316	316	FKM
	D	HC-276	316	316	Glass-filled PTFE
Low pressure side clamp flange process connection		Specifications	Drain/vent valve position	Thread	Mounting method
	2	Female 1/4-18NPT	Above the side of flange	7/16-20UNF (F)	Horizontal
	3	Female 1/4-18NPT	Under the side of flange	7/16-20UNF(F)	Horizontal
					
Low pressure side fill oil		S Normal temperature silicone oil (Medium temperature : -40℃ ~205℃ ,diaphragm ambient environment: -40℃ ~85℃)			
	D	Inert oil (Medium temperature : -45℃ ~160℃ ,diaphragm ambient environment: -40℃ ~85℃)			
	H	High temperature silicone oil (Medium temperature: 0℃ ~315℃ , diaphragm ambient environment: 0℃ ~85℃)			
Clamp flange fastener	6	Bolts, nuts and other assemblies, 316 SS			
Diaphragm connection position	H	Differential pressure transmitter high pressure side			
Diaphragm seal system code	M	Side mounted movable flange insertion sleeve			
Flange standard	2	HG/T-20592			
	1	EN1092-1			
	5	HG/T-20615			
	6	ANSI/ASME B16.5			
Flange diameter		Applicable standard			
	B	DN50	HG/T-20592, EN1092-1		
	C	DN80	HG/T-20592, EN1092-1		
	D	DN100	HG/T-20592, EN1092-1		
	2	2inch	HG/T-20615, ANSI/ASME B16.5		
	3	3inch	HG/T-20615, ANSI/ASME B16.5		
	4	4inch	HG/T-20615, ANSI/ASME B16.5		
Pressure class		Applicable standard			Applicable flange diameter
	1	PN10/PN16	HG/T-20592, EN1092-1		DN50, DN80, DN100
	2	PN25/PN40	HG/T-20592, EN1092-1		DN50, DN80, DN100
	3	PN63	HG/T-20592, EN1092-1		DN50, DN80
	4	PN100	HG/T-20592, EN1092-1		DN50, DN80
	A	Class 150	HG/T-20615, ANSI/ASME B16.5		2inch, 3inch, 4inch
	B	Class 300	HG/T-20615, ANSI/ASME B16.5		2inch, 3inch, 4inch
	C	Class 600	HG/T-20615, ANSI/ASME B16.5		2inch, 3inch
Note: The maximum static pressure or overload depends on the flange pressure class					
Flange material	6	316 SS			
Blind sealing surface	1	RF Raised surface			
	A	FM Concave surface			
	B	M Convex surface			
	C	RJ Annular connection surface			
Note: For details about FM concave, M convex, RJ annular connection surface, please consult the engineer					
Insertion sleeve diameter		Applicable flange diameter			
	4	46mm	DN50, 2inch		
	6	66mm	DN80, 3inch		
	7	77mm	DN100, 4inch		



Insertion sleeve length	A	50mm
	B	100mm
	C	150mm
	D	200mm
Insertion sleeve material	6	316 SS
Wetted parts material	Please see the material list of wetted parts for details	
	Blind	Measuring diaphragm
6A	316 SS	316L
6B	316 SS	Hastelloy C-276
6C	316 SS	Tantalum
6D	316 SS	Titanium
6E	316 SS	Monel
High pressure side fill oil	S	Normal temperature silicone oil (Medium temperature : -40°C ~205°C ,diaphragm ambient environment: -40°C ~85°C)
	D	Inert oil (Medium temperature : -45°C ~160°C ,diaphragm ambient environment: -40°C ~85°C)
	H	High temperature silicone oil (Medium temperature: 0°C ~315°C ,diaphragm ambient environment: 0°C ~85°C)
Factory calibration range	CAL	Provides Micro Sensor standard verification report according to the range, and the default linear output Contract specifies: LRL - URL, display unit*
Options	Description (Detailed specifications as following, multiple options or null)	
High vacuum high temperature	/V	High vacuum and high temperature process diaphragm (if this option is selected, the accuracy will be affected and can only up to 0.2%)
Process connection accessories	/D1	T-shaped adapter (M) M20×1.5 and vent tube Φ14mm× 2mm× 30mm, 316 SS
	/D2	Waist-shaped adapter, 1/2-14NPT (F), 316SS
Verification report	/Q1	Provide the Micro Sensor verification data according to user requirements Contract specifies: LRL - URL, display unit*
Note: Standard format follows the Micro Sensor's specifications. Select this option and provide the template if the customer specifies a format		
Damping time setting	/ST	Adjustable range 0s~100s, default 0s Contract specifies: Damping time*
Fault alarm setting	/WH	High alarm current value, 20.8mA
	/WL	Low alarm current value, 3.8mA, default
	/WS	Other saturation current values, specified within the range of 3.6mA~3.8mA or 20mA~22mA Contract specifies: saturation current values *
Product certificate	/QE	Standard format follows the Micro Sensor's specifications. Select this option and provide the template if the customer specifies a format
Identification plate	/PT	Product is shipped with an identification plate Contract specifies: Identification number, not exceeding 16 characters
Integrated valve manifold	/VT	Differential pressure transmitter is factory assembled with Micro Sensor valve manifold See attachment for order guide of valve manifold Contract specifies: Complete model of Micro Sensor valve manifold*
Leakage test report	/QD4	PN10/PN16 (class150) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD5	PN25/PN40 (class300) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD6	PN63, Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD7	PN100 (class600) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report

Note: The test pressure is the same as the flange pressure class

HART configuration	/H5	HART5 configuration	
Diaphragm with gold plated	/J3	Single diaphragm on high pressure side (5μ)	
	/J4	Double diaphragms on high and low pressure sides (5μ)	
Diaphragm spraying	/T3	High pressure side single flange	
Oil-free treatment	/CL1	Degreasing and cleaning treatment of the wetted parts	
Note: Please check the fill oil. Determine whether the inert filling oil is required (code: D).			

Certificates	/CS1	CCS, China Classification Society , TJ23PTB00014	
	/CS2	DNV, Det Norske Veritas	
	/CS3	BV, Bureau Veritas	
	/CS4	ABS, American Bureau of Shipping	
	/CS5	LR, Lloyd's Register of Shipping	
	/CS6	KR, Korean Register of Shipping	
	/CS7	NK, Nippon Kaiji Kyokai	
	/CS8	RS, Russian Maritime Register of Shipping	

Note: Except for the CCS certificate, please consult the engineer for others.

Lithium battery	/LD	General requirements for low copper and zinc in the lithium battery industry	
High-accuracy	/HAC	High-accuracy calibration according to the user's specified range Contract specifies: Range of use (within sensor's limit), LRL - URL, display unit, accuracy*	
Language	/LE	English nameplate, operation manual, product certificate, etc.	
Delivery service	/XM	Provide customer requested content according to project delivery standards	
Extended warranty period	/Y3	3-year warranty	
	/Y5	5-year warranty	

***Note:** The specifications required for these options should be specified in the contract.

Example: MDM7000-LT-1HP1L-2A1S1-HM-2B14614A66AS/D1- 【CAL: 0-0.4bar】

|| Order Guide ||

MDM7000-LT — □□□□□ — □ — HF — □□□□□□□□ — □□□□□


Body

Remote Fixed Flange Diaphragm

Item	Code	Description			
MDM7000-LT	—	Monocrystalline Silicon Differential Pressure Transmitter With Remote Diaphragm Seal (Remote Fixed Flange)			
Application of hazardous area					
	1	China, Flameproof certificate, No.CE23.6650 Ex db IIC T6 Gb, GB/T3836.1-2021, GB/T3836.2-2021			
	2	China, Intrinsically safe certificate, No.CE23.7688X Ex ia IIC T4 Ga, GB/T3836.1-2021, GB/T3836.4-2021			
	3	China, Dust explosion-proof certificate, GYB24.1215X Ex tb III C T85°C Db, GB/T3836.1-2021, GB/T 3836.31-2021			
	4	China, Flameproof certificate, Intrinsically safe certificate			
	A	CSA, Flameproof certificate			
	B	CSA, Intrinsically safe certificate			
	C	CSA, Flameproof certificate, Intrinsically safe certificate			
	E	ATEX, Flameproof certificate			
	F	ATEX, Intrinsically safe certificate			
	G	ATEX, Flameproof certificate, Intrinsically safe certificate			
	J	IECEx, Flameproof certificate	 		
	K	IECEx, Intrinsically safe certificate			
	L	IECEx, Flameproof certificate, Intrinsically safe certificate			
	0	Non-hazardous area			
	T	Other certificate			
Output signal	H	4mA~20mA DC, HART			
Case	S	Stainless steel case with two outlet ports (F) M20×1.5			
	U	Stainless steel case with two outlet ports (F) 1/2NPT			
	P	Aluminum alloy case with two outlet ports (F) M20×1.5			
	N	Aluminum alloy case with two outlet ports (F) 1/2NPT			
Note: Please pay attention to the item of lithium battery (Code: LD)					
Waterproof/explosion-proof connector					
		Specification	Material		
	1	M20×1.5 waterproof connector, with plug	PVC		
	2	Non-flameproof adapter (F) M20×1.5, with plug	316 SS		
	3	Flameproof adapter (F) 1/2NPT, with plug	316 SS		
	4	Flameproof adapter (F) M20×1.5, with plug	316 SS		
	5	Flameproof adapter (F) G1/2, with plug	316 SS		
		Applicable wire diameter	IP rating		
	1	6mm~8mm	IP67		
	2	6mm~8mm	IP67		
	3	6mm~8mm	IP67		
	4	6mm~8mm	IP67		
	5	6mm~8mm	IP67		
Note: Flameproof configuration is applicable to PCEC/ATEX/IECEx standards. Flameproof adapter with CCC certificate. Please contact the engineer if double sealing is required.					
Display	N	Without LCD display			
	L	Display module, -20°C ~70°C			
Sensor module range					
		Nominal range	Minimum range	Lower (LRL)	Upper (URL)
	2	0.4bar	0.1bar	-0.4bar	0.4bar
	3	2.5bar	0.25bar	-2.5bar	2.5bar

Low pressure side wetted parts

		Diaphragm	Flange block	Discharge valve/plug	Sealings
	A	316L	316	316	FKM
	B	316L	316	316	Glass-filled PTFE
	C	HC-276	316	316	FKM
	D	HC-276	316	316	Glass-filled PTFE
Low pressure side clamp flange process connection		Specifications	Drain/vent valve position	Thread	Mounting method
	2	Female 1/4-18NPT	Above the side of flange	7/16-20UNF (F)	Horizontal
	3	Female 1/4-18NPT	Under the side of flange	7/16-20UNF(F)	Horizontal
Low pressure side fill oil	S	Normal temperature silicone oil (Medium temperature : -40°C ~205°C ,diaphragm ambient environment: -40°C ~85°C)			
	D	Inert oil (Medium temperature : -45°C ~160°C ,diaphragm ambient environment: -40°C ~85°C)			
	H	High temperature silicone oil (Medium temperature: 0°C ~315°C , diaphragm ambient environment: 0°C ~85°C)			
Clamp flange fastener	6	Bolts, nuts and other assemblies, 316 SS			
Diaphragm connection position	H	Differential pressure transmitter high pressure side			
Diaphragm seal system code	F	Remote fixed flange			
Flange standard	2	HG/T-20592			
	1	EN1092-1			
	5	HG/T-20615			
	6	ANSI/ASME B16.5			
Flange diameter		Applicable standard			
	B	DN50	HG/T-20592, EN1092-1		
	C	DN80	HG/T-20592, EN1092-1		
	D	DN100	HG/T-20592, EN1092-1		
	2	2inch	HG/T-20615, ANSI/ASME B16.5		
	3	3inch	HG/T-20615, ANSI/ASME B16.5		
	4	4inch	HG/T-20615, ANSI/ASME B16.5		
Pressure class			Applicable standard		Applicable flange diameter
	1	PN10/PN16	HG/T-20592, EN1092-1		DN50, DN80, DN100
	2	PN25/PN40	HG/T-20592, EN1092-1		DN50, DN80, DN100
	3	PN63	HG/T-20592, EN1092-1		DN50, DN80
	4	PN100	HG/T-20592, EN1092-1		DN50, DN80
	A	Class 150	HG/T-20615, ANSI/ASME B16.5		2inch, 3inch, 4inch
	B	Class 300	HG/T-20615, ANSI/ASME B16.5		2inch, 3inch, 4inch
	C	Class 600	HG/T-20615, ANSI/ASME B16.5		2inch, 3inch
Note: The maximum static pressure or overload depends on the flange pressure class					
Flange material	6	316 SS			
Flange sealing surface	1	RF Raised surface			
	A	FM Concave surface			
	B	M Convex surface			
	C	RJ Annular connection surface			
Note: For details about FM concave, M convex, RJ annular connection surface, please consult the engineer					
Insertion sleeve material	6	316 SS			



Wetted parts material		Please see the material list of wetted parts for details		
		Blind	Measuring diaphragm	
	6A	316 SS	316L	
	6B	316 SS	Hastelloy C-276	
	6C	316 SS	Tantalum	
	6D	316 SS	Titanium	
	6E	316 SS	Monel	
Capillary connection location	K	Rear connection		
Capillary type	U	3.5mm OD (or 1/8 inch), armored 316L SS, PVC gray sheath		
	L	3.5mm OD (or 1/8 inch), armored 316L SS, stainless steel bellows sheath		
Capillary length		Applicable flange diameter		
		DN50/2inch	DN80/3inch	DN100/4inch
	1	1m		
	2	2m		
	3	3m		
	4	4m		
	5	5m		
	6	6m	×	
	7	7m	×	
	8	8m	×	
	9	9m	×	
	A	10m	×	
Note: "×" means unavailable; the part beyond the length will be selected according to the next level of meters.				
High pressure side fill oil	S	Normal temperature silicone oil (Medium temperature : -40℃ ~205℃ , diaphragm ambient environment: -40℃ ~85℃)		
	D	Inert oil (Medium temperature: -45℃ ~160℃ ,diaphragm ambient environment:-40℃ ~85℃)		
	H	High temperature silicone oil (Medium temperature: 0℃ ~315℃ , diaphragm ambient environment: 0℃ ~85℃)		
Factory calibration range	CAL	Provides Micro Sensor standard verification report according to the range, and the default linear output Contract specifies: LRL - URL, display unit*		
Options		Description (Detailed specifications as following, multiple options or null)		
High vacuum high temperature	/V	High vacuum and high temperature process diaphragm (if this option is selected, the accuracy will be affected and can only up to 0.2%)		
Mounting bracket	/G1	Bent bracket, 316 SS		
Process connection accessories	/D1	T-shaped adapter (M) M20×1.5 and vent tube Φ14mm× 2mm× 30mm, 30, 316 SS		
	/D2	Waist-shaped adapter, 1/2-14NPT (F), 316SS		
Verification report	/Q1	Provide the Micro Sensor verification data according to user requirements Contract specifies: LRL - URL, display unit*		
Note: Standard format follows the Micro Sensor's specifications. Select this option and provide the template if the customer specifies a format				
Damping time setting	/ST	Adjustable range 0s~100s, default 0s Contract specifies: Damping time*		

Fault alarm setting	/WH	High alarm current value, 20.8mA
	/WL	Low alarm current value, 3.8mA, default
	/WS	Other saturation current values, specified within the range of 3.6mA~3.8mA or 20mA~22mA Contract specifies: saturation current values *
Product certificate	/QE	Standard format follows the Micro Sensor's specifications. Select this option and provide the template if the customer specifies a format
Identification plate	/PT	Product is shipped with an identification plate Contract specifies: Identification number, not exceeding 16 characters
Integrated valve manifold	/VT	Differential pressure transmitter is factory assembled with Micro Sensor valve manifold See attachment for order guide of valve manifold Contract specifies: Complete model of Micro Sensor valve manifold*
Leakage test report	/QD4	PN10/PN16 (class150) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD5	PN25/PN40 (class300) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD6	PN63, Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD7	PN100 (class600) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
Note: The test pressure is the same as the flange pressure class		
HART configuration	/H5	HART5 configuration
Diaphragm with gold plated	/J3	Single diaphragm on high pressure side (5μ)
	/J4	Double diaphragms on high and low pressure sides (5μ)
Diaphragm spraying	/T1	High pressure side single flange
Diaphragm sticking	/PFA	The diaphragm is stuck with PFA film, applicable to non-vacuum situations (pressure ≥ 0)
Oil-free treatment	/CL1	Degreasing and cleaning treatment of the wetted parts
Note: Please check the fill oil. Determine whether the inert filling oil is required (code: D).		
Certificates	/CS1	CCS, China Classification Society, TJ23PTB00014
	/CS2	DNV, Det Norske Veritas
	/CS3	BV, Bureau Veritas
	/CS4	ABS, American Bureau of Shipping
	/CS5	LR, Lloyd's Register of Shipping
	/CS6	KR, Korean Register of Shipping
	/CS7	NK, Nippon Kaiji Kyokai
	/CS8	RS, Russian Maritime Register of Shipping
Note: Except for the CCS certificate, please consult the engineer for others.		
Lithium battery	/LD	General requirements for low copper and zinc in the lithium battery industry
High-accuracy	/HAC	High-accuracy calibration according to the user's specified range Contract specifies: Range of use (within sensor's limit), LRL - URL, display unit, accuracy*
Language	/LE	English nameplate, operation manual, product certificate, etc.
Delivery service	/XM	Provide customer requested content according to project delivery standards
Extended warranty period	/Y3	3-year warranty
	/Y5	5-year warranty



***Note:** The specifications required for these options should be specified in the contract.


Example: MDM7000-LT-1HP1L-2A1S1-HF-2B1614AKU3S/D1- 【CAL: 0-0.4bar】

|| Order Guide ||

MDM7000-LT — □□□□□ — □ — HE — □□□□□□□□ — □□□□□

Body

Remote Fixed Flange Insertion Sleeve Diaphragm

Item	Code	Description				
MDM7000-LT	—	Monocrystalline Silicon Differential Pressure Transmitter With Remote Diaphragm Seal (Remote Fixed Flange Insertion Sleeve)				
Application of hazardous area						
	1	China, Flameproof certificate, No.CE23.6650 Ex db IIC T6 Gb, GB/T3836.1-2021, GB/T3836.2-2021				
	2	China, Intrinsically safe certificate, No.CE23.7688X Ex ia IIC T4 Ga, GB/T3836.1-2021, GB/T3836.4-2021				
	3	China, Dust explosion-proof certificate, GYB24.1215X Ex tb III C T85°C Db, GB/T3836.1-2021, GB/T 3836.31-2021				
	4	China, Flameproof certificate, Intrinsically safe certificate				
	A	CSA, Flameproof certificate				
	B	CSA, Intrinsically safe certificate				
	C	CSA, Flameproof certificate, Intrinsically safe certificate				
	E	ATEX, Flameproof certificate				
	F	ATEX, Intrinsically safe certificate				
	G	ATEX, Flameproof certificate, Intrinsically safe certificate				
	J	IECEx, Flameproof certificate	 			
	K	IECEx, Intrinsically safe certificate				
	L	IECEx, Flameproof certificate, Intrinsically safe certificate				
	0	Non-hazardous area				
	T	Other certificate				
Output signal	H	4mA~20mA DC, HART				
Case	S	Stainless steel case with two outlet ports (F) M20×1.5				
	U	Stainless steel case with two outlet ports (F) 1/2NPT				
	P	Aluminum alloy case with two outlet ports (F) M20×1.5				
	N	Aluminum alloy case with two outlet ports (F) 1/2NPT				
Note: Please pay attention to the item of lithium battery (Code: LD)						
Waterproof/explosion-proof connector						
		Specification	Material	Applicable wire diameter	IP rating	
	1	M20×1.5 waterproof connector, with plug	PVC	6mm~8mm	IP67	
	2	Non-flameproof adapter (F) M20×1.5, with plug	316 SS	6mm~8mm	IP67	
	3	Flameproof adapter (F) 1/2NPT, with plug	316 SS	6mm~8mm	IP67	
	4	Flameproof adapter (F) M20×1.5, with plug	316 SS	6mm~8mm	IP67	
	5	Flameproof adapter (F) G1/2, with plug	316 SS	6mm~8mm	IP67	
Note: Flameproof configuration is applicable to PCEC/ATEX/IECEx standards. Flameproof adapter with CCC certificate. Please contact the engineer if double sealing is required.						
Display	N	Without LCD display				
	L	Display module, -20°C ~70°C				
Sensor module range						
		Nominal range	Minimum range	Lower (LRL)	Upper (URL)	
	2	0.4bar	0.1bar	-0.4bar	0.4bar	
	3	2.5bar	0.25bar	-2.5bar	2.5bar	

Low pressure side wetted parts

		Diaphragm	Flange block	Discharge valve/plug	Sealings
	A	316L	316	316	FKM
	B	316L	316	316	Glass-filled PTFE
	C	HC-276	316	316	FKM
	D	HC-276	316	316	Glass-filled PTFE

Low pressure side clamp flange process connection		Specifications	Drain/vent valve position	Thread	Mounting method
	2	Female 1/4-18NPT	Above the side of flange	7/16-20UNF (F)	Horizontal
	3	Female 1/4-18NPT	Under the side of flange	7/16-20UNF(F)	Horizontal



Low pressure side fill oil	S	Normal temperature silicone oil (Medium temperature : -40°C ~205°C ,diaphragm ambient environment: -40°C ~85°C)			
	D	Inert oil (Medium temperature : -45°C ~160°C ,diaphragm ambient environment: -40°C ~85°C)			
	H	High temperature silicone oil (Medium temperature: 0°C ~315°C , diaphragm ambient environment: 0°C ~85°C)			

Clamp flange fastener	6	Bolts, nuts and other assemblies, 316 SS			
-----------------------	---	--	--	--	--

Diaphragm connection position	H	Differential pressure transmitter high pressure side			
Diaphragm seal system code	E	Remote fixed flange insertion sleeve			

Flange standard	2	HG/T-20592			
	1	EN1092-1			
	5	HG/T-20615			
	6	ANSI/ASME B16.5			

Flange diameter		Applicable standard			
	B	DN50	HG/T-20592, EN1092-1		
	C	DN80	HG/T-20592, EN1092-1		
	D	DN100	HG/T-20592, EN1092-1		
	2	2inch	HG/T-20615, ANSI/ASME B16.5		
	3	3inch	HG/T-20615, ANSI/ASME B16.5		
	4	4inch	HG/T-20615, ANSI/ASME B16.5		

Pressure class			Applicable standard	Applicable flange diameter
	1	PN10/PN16	HG/T-20592, EN1092-1	DN50, DN80, DN100
	2	PN25/PN40	HG/T-20592, EN1092-1	DN50, DN80, DN100
	3	PN63	HG/T-20592, EN1092-1	DN50, DN80
	4	PN100	HG/T-20592, EN1092-1	DN50, DN80
	A	Class 150	HG/T-20615, ANSI/ASME B16.5	2inch, 3inch, 4inch
	B	Class 300	HG/T-20615, ANSI/ASME B16.5	2inch, 3inch, 4inch
	C	Class 600	HG/T-20615, ANSI/ASME B16.5	2inch, 3inch

Note: The maximum static pressure or overload depends on the flange pressure class

Flange material	6	316 SS			
-----------------	---	--------	--	--	--

Flange sealing surface	1	RF Raised surface			
	A	FM Concave surface			
	B	M Convex surface			
	C	RJ Annular connection surface			

Note: For details about FM concave, M convex, RJ annular connection surface, please consult the engineer

Insertion sleeve diameter		Applicable flange diameter			
	4	46mm	DN50, 2inch		
	6	66mm	DN80, 3inch		
	7	77mm	DN100, 4inch		

Insertion sleeve length	A	50mm						
	B	100mm						
	C	150mm						
	D	200mm						
Insertion sleeve material	6	316 SS						
Wetted parts material		Please see the material list of wetted parts for details						
		Blind	Measuring diaphragm					
	6A	316 SS	316L					
	6B	316 SS	Hastelloy C-276					
	6C	316 SS	Tantalum					
	6D	316 SS	Titanium					
	6E	316 SS	Monel					
Capillary connection location	K	Rear connection						
Capillary type	U	3.5mm OD (or 1/8 inch), armored 316L SS, PVC gray sheath						
	L	3.5mm OD (or 1/8 inch), armored 316L SS, stainless steel bellows sheath						
Capillary length		Insertion sleeve diameter		Adaptable measuring diaphragm				
				6A-316L	6B-HastelloyC-276	6C-Tantalum	6D-Titanium	6E-Monel
	1	1m	S-46mm					
M-66mm								
L-77mm								
	2	2m	S-46mm					
M-66mm								
L-77mm								
	3	3m	S-46mm					
M-66mm								
L-77mm								
	4	4m	S-46mm			x	x	x
M-66mm								
L-77mm								
	5	5m	S-47mm			x	x	x
M-66mm								
L-77mm								
	6	6m	M-66mm					
L-77mm								
	7	7m	M-66mm					
L-77mm								
	8	8m	M-66mm					
L-77mm								
	9	9m	M-66mm					
L-77mm								
	A	10m	M-66mm					
L-77mm								

Note: "x" means unavailable; the part beyond the length will be selected according to the next level of meters.

High pressure side fill oil	S	Normal temperature silicone oil (Medium temperature : -40°C ~205°C , diaphragm ambient environment: -40°C ~85°C)
	D	Inert oil (Medium temperature: -45°C ~160°C ,diaphragm ambient environment:-40°C ~85°C)
	H	High temperature silicone oil (Medium temperature: 0°C ~315°C , diaphragm ambient environment: 0°C ~85°C)
Factory calibration range	CAL	Provides Micro Sensor standard verification report according to the range, and the default linear output Contract specifies: LRL - URL, display unit*
Options		Description (Detailed specifications as following, multiple options or null)
High vacuum high temperature	/V	High vacuum and high temperature process diaphragm (if this option is selected, the accuracy will be affected and can only up to 0.2%)
Mounting bracket	/G1	Bent bracket, 316 SS
Process connection accessories	/D1	T-shaped adapter (M) M20×1.5 and vent tube Φ14mm× 2mm× 30mm, 30, 316 SS
	/D2	Waist-shaped adapter, 1/2-14NPT (F), 316SS
Verification report	/Q1	Provide the Micro Sensor verification data according to user requirements Contract specifies: LRL - URL, display unit*
Note: Standard format follows the Micro Sensor's specifications. Select this option and provide the template if the customer specifies a format		
Damping time setting	/ST	Adjustable range 0s~100s, default 0s Contract specifies: Damping time*
Fault alarm setting	/WH	High alarm current value, 20.8mA
	/WL	Low alarm current value, 3.8mA, default
	/WS	Other saturation current values, specified within the range of 3.6mA~3.8mA or 20mA~22mA Contract specifies: saturation current values *
Product certificate	/QE	Standard format follows the Micro Sensor's specifications. Select this option and provide the template if the customer specifies a format
Identification plate	/PT	Product is shipped with an identification plate Contract specifies: Identification number, not exceeding 16 characters
Integrated valve manifold	/VT	Differential pressure transmitter is factory assembled with Micro Sensor valve manifold See attachment for order guide of valve manifold Contract specifies: Complete model of Micro Sensor valve manifold*
Leakage test report	/QD4	PN10/PN16 (class150) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD5	PN25/PN40 (class300) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD6	PN63, Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
	/QD7	PN100 (class600) , Nitrogen (N2) or air, pressure holding for 10 minutes, provide Micro Sensor standard leakage test report
Note: The test pressure is the same as the flange pressure class		
HART configuration	/H5	HART5 configuration
Diaphragm with gold plated	/J3	Single diaphragm on high pressure side (5μ)
	/J4	Double diaphragms on high and low pressure sides (5μ)
Diaphragm spraying	/T3	High pressure side single insertion sleeve
Oil-free treatment	/CL1	Degreasing and cleaning treatment of the wetted parts
Note: Please check the fill oil. Determine whether the inert filling oil is required (code: D).		



Certificates	/CS1	CCS, China Classification Society, TJ23PTB00014
	/CS2	DNV, Det Norske Veritas
	/CS3	BV, Bureau Veritas
	/CS4	ABS, American Bureau of Shipping
	/CS5	LR, Lloyd's Register of Shipping
	/CS6	KR, Korean Register of Shipping
	/CS7	NK, Nippon Kaiji Kyokai
	/CS8	RS, Russian Maritime Register of Shipping



Note: Except for the CCS certificate, please consult the engineer for others.

Lithium battery	/LD	General requirements for low copper and zinc in the lithium battery industry
High-accuracy	/HAC	High-accuracy calibration according to the user's specified range Contract specifies: Range of use (within sensor's limit), LRL - URL, display unit, accuracy*
Language	/LE	English nameplate, operation manual, product certificate, etc.
Delivery service	/XM	Provide customer requested content according to project delivery standards
Extended warranty period	/Y3	3-year warranty
	/Y5	5-year warranty

***Note:** The specifications required for these options should be specified in the contract.

Example: MDM7000-LT-1HP1L-2A1S1-HE-2B1614A6AKU3S/G1- 【CAL: 0-0.4bar】

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47